



CITYCOLOR 2500 IP54 (CYM System)

SOURCE

MSA/DE 2500W
Lamp life 2.000 hours
Color temperature 6.000 K
Luminous flux 260.000 lm

• OPTIC COLOR SYSTEM

Full CYM color mixing, unlimited variety of colours and shades.
High resolution stepper motors
The color changer can be driven with 4 different speeds or in real time
Shutter + dimmer

• BEAM ANGLE (50% intensity)

50°x52°

• HEAD ROTATION

Up to 260°

• CONTROL INPUT

Standard interface: RS-485; opto-couplet input
Protocol: USITT DMX 512
Software upgrade from DMX line

• SETUP AND CONFIGURATION

Dynamic menus for customization of all fixture functions

• AUTO MODE

Stand-alone control: auto mode function master/slave (synchro mode) with internal preset

• IP 54 RATE

• POWER SUPPLY (magnetic ballast)

Rated voltage: 230V~ /50Hz
On request:
200V~ /50Hz; 208V~ /60Hz; 230V~ /60Hz; 240V~ /50Hz
Rated current: 14A @ 230V
Rated power: 2700W

• POWER FACTOR CORRECTOR: built-in cos Ø 0.9

• ELECTRONICALLY FAN CONTROL to reduce the noise

• STAND-BY FUNCTION to power off all power circuits

• DMX CHANNELS

7 channels

• **PHYSICAL**

WxDxH: 780x560x740 mm

Weight: 69 kg.