Light Source:

- LED Qty.: 3 x White (60W)
- Drive Current: 12A

Electrical:

- Input Voltage: 100 ~ 240V...50/60Hz
- Max. Power: 250W

Control:

- On-board: Display for Auto and Custom control
- Protocol: DMX512
- Personality: Advanced(18CHS) / Basic(13CHS)

Movement:

- Pan: 540°
- Tilt: 270°
- Pan/Tilt Resolution: 8 16 bit
- Special: Pan/Tilt movement blackout User-selectable pan/tilt ranges

Gobos & Colors:

- Rotating Gobo: 6 Gobos, Gobo-flow effect, Gobo shake, Bi-directional rotation
- Static Gobos: 7 metal Gobos
- Colors: 7 dichroic-filters + White, Rainbow-flow effect

Physical:

- Dimensions: 408 x 296 x 606mm
- Weight: 19kg
- Housing: Flame-retardant plastic(V0)
- Color: Black
- Fixture Connection: Data in/out, Power in
- Cooling: Forced Convection

Certification and Safety:

- Certification: CE, cETL
- Environment: Dry location
- Operation Temperature: -20°C ~ 45°C

Output:

- Max. Flux: 3649lm
- Peak Intensity: 81636cd

Optical System:

• Dimmer: 0 - 100%

- Strobe: 0 20Hz
- Optics: 20°
- Prism: Rotating 3-facet prism

•