AKG C411 PICKUP MICROPHONE

General Specifications		Dimensions	
Туре	Pre-polarized condenser transducer	Length	9.7 mm
Polar Pattern	Figure of eight	Width	14.2 mm
Audio frequency bandwidth	10 - 18000 Hz	Height	26.7 mm
Sensitivity	2 mV/Pa	Net Weight	18 g (0.6 oz.)
Electrical impedance	200 Ohms	Cable length	1.5 m (5 ft.)
Recommended load impedance	1000 Ohms		
Max. SPL for 1%/3% THD	96 dB / 103 dB	Design	
Current consumption	approx. 2.2 mA	Body	plastic
		Finish	matte black
Audio Output		Powering Interface	
Туре	Mini XLR	Voltage	9 to 52 V
Gender	Female	Current	2 mA
Contacts	3-pin		
		Application	
		Live Instrument	Yes
Instrument			
Piano / Strings	Vac		

AKG C411 PICKUP MICROPHONE

9.7 mm 14.2 mm 26.7 mm 18 g (0.6 oz.) 1.5 m (5 ft.)

plastic matte black

> 9 to 52 V 2 mA

> > Yes

General Specifications		Dimensions
Туре	Pre-polarized condenser transducer	Length
Polar Pattern	Figure of eight	Width
Audio frequency bandwidth	10 - 18000 Hz	Height
Sensitivity	2 mV/Pa	Net Weight
Electrical impedance	200 Ohms	Cable length
Recommended load impedance	1000 Ohms	
Max. SPL for 1%/3% THD	96 dB / 103 dB	Design
Current consumption	approx. 2.2 mA	Body
		Finish
Audio Output		Powering Interface
Туре	Mini XLR	Voltage
Gender	Female	Current
Contacts	3-pin	
		Application
		Live Instrument
Instrument		



AKG C411 PICKUP MICROPHONE

General Specifications		Dimensions	
Туре	Pre-polarized condenser transducer	Length	9.7 mm
Polar Pattern	Figure of eight	Width	14.2 mm
Audio frequency bandwidth	10 - 18000 Hz	Height	26.7 mm
Sensitivity	2 mV/Pa	Net Weight	18 g (0.6 oz.)
Electrical impedance	200 Ohms	Cable length	1.5 m (5 ft.)
Recommended load impedance	1000 Ohms		
Max. SPL for 1%/3% THD	96 dB / 103 dB	Design	
Current consumption	approx. 2.2 mA	Body	plastic
		Finish	matte black
Audio Output		Powering Interface	
Туре	Mini XLR	Voltage	9 to 52 V
Gender	Female	Current	2 mA
Contacts	3-pin		
		Application	
		Live Instrument	Yes
Instrument			
Piano / Strings	Vac		